Transportation & Weighing in one step Fast and Precise Weighing Industrial and Warehousing Applications Battery Powered

PTS Pallet Truck Scale



PTS Pallet Truck Scale A Combination of Transportation & Weighing

General Information

Indicator Box

Mettler-Toledo Pallet Truck Scale integrates the indicator PCB, J-Box PCB, battery and charging circuit into the indicator box, rechargeable battery powered with a charger.

Load Cell

Four strain gauge shear beam load cells mounted in the forks.

Pallet Truck

- Hydraulic lift and low
- Tandem load wheels
- Steering wheels and load wheels: polyurethane
 Oil leakage rate: less than 0.1%.

Specifications

Product Model	SCS-2C			
Lifting capacity	2000 kg			
Weighing range	2000 kg			
Accuracy				
Temperature range	-10°C~+40°C			
Load cell capacity	1 ton x 4			
Single fork width	180 mm			
Lifting Height	115mm			
Fork Height, lowered / Raised	85mm/200mm			
Battery (with charger)	6VDC, 10Ah, Operating time: 55~60h			
(overcharging is permitted)	charging time: 8~12h			

Standard Size and Capacity

Product Code	Weighing range	Increment	Lowered fork height	Width over the forks	Fork length	Package Size (mm)	Shipment Weight
PTS20-0001	2.0t	2kg	85mm	555mm	1150mm	1620x600x1000	150kg
PTS20-0004	2.0t	2kg	85mm	690mm	1220mm	1700x730x1000	170kg

Notes: 1) The scale is provided in ORANGE PANTONE with BLACK lifting system and forks.







METTLER TOLEDO